THIRD—ORDER LEVELING
SEA LEVEL DATUM OF 1929

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY


37-085-42
HODGENVILLE QUADRANGLE
125 KENTUCKY
N3730-W8530/15
DIAGRAM NJ 16-9
WINCHESTER

Hardin, Larue, Marion and Melson Counties

Final adjustment of 1952

Edition of 4/17/74

PR: WSM/mjh



ELIZABETHTOWN (126)

MGS (USC&GS) VERTICAL CONTROL DATA

A. Quadrangle 370854

LEBANON (124)

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	MARK (USGS)	PAGE NO.
TT 7 E 1930 634	4,6	137 JEM 1950 908	9
TT 8 E 1930	4	138 JEM 1950 854	ģ
TT 9 E 1930	4	140 JEM 1950 920	. 9
TT 4 TN 1933 469	3	141 JEM 1950 940	ģ
TT 5 TN 1933 953	3,8	142 JEM 1950 878	ģ
TT 6 TN 1933 869	3	143 JEM 1950 779	9,10
TT 13 TN 1933 811	3	146 JEM 1950 937 RESET 1952	10,10
TT 21 TN 1933 730	3,9	147 JEM 1950 839	10
TT 22 TN 1933 RESET 1958	3	TT 28 AS 1950 667	6
12 JWM 1948 506	4	TT 29 AS 1950 528	6
13 JwM 1948 591	4	TT 30 AS 1950 682	6
119 JEM 1950 932	4	TT 31 AS 1950 561	5
120 JEM 1950 929	4,6	TT 32 AS 1950 570	5
121 JEM 1950 544	5	TT 51 AS 1950	5
122 JEM 1950 879	5	NO 2	9
123 JEM 1950 904	5		
124 JEM 1950 604	7	NGS	
125 JEM 1950 960	7		
126 JEM 1950 874	7	J 58 1935	4
127 JEM 1950 519	6	L 58 1935	10
128 JEM 1950 515	6,10	P 58 1935	10
129 JEM 1950 522	6,8	H 60 1935	4
130 JEM 1950 519	7	K 60 1935	8,9
131 JEM 1950 479	7	M 60 1935	7
132 JEM 1950 463	8	Q 60 1935	6,7
133 JEM 1950 496	8		
134 JEM 1950 838	8		
135 JEM 1950 893	8,8		
136 JEM 1950 983	9,9		

770.67

1933

LINE 1. Feet By D. C. Antrobus, 1933; Book B 5084 Darlington School, 2.2 mi S. of; 10 ft M. of junction of Younger Creek Road and I-rd. S. to Ballinger School; 1 ft S. of John A. Wallace's fenceline; in concrete post; standard tablet stamped "IT 4 TN 1933 469" < PO < Ted destroyed 1982 468.543 Reference mark; 600 ft NE. of tablet; 120 ft NW. of rd.; in root on SE. side of 30-in. wateroak tree; copper nail and washer 463.23 Ballinger School; 140 ft NW. of; 8.0 mi E. of Elizabethtown; 80 ft S. and 140 ft E. of junction of Elizabethtown-Springfield Road and T-rd. S. to Middle Creek; in concrete post; standard tablet stamped "TI 5 IN 1933 953" Cep of teach destroyed 1982 952.469 Reference mark; 560 ft NW. of tablet; 10 ft S. of rd.; in root on N. side of 18-in. white-oak tree; copper nail and washer 927.63 Middle Creek; 25 ft N. and 40 ft W. of crossroads; in S. corner of John Edlin's pasture field; in concrete post; standard tablet stamped "TT 6 TN 1933 869" 869.242 Reference mark; 730 ft N. of tablet; 100 ft N. of top; 12 ft E. of center of rd.; in root on E. side of 18-in. locust tree; copper nail and washer 891.97 Hodgenville, 3.0 mi M. of; on Hodgenville-Shepherdsville Road; 75 ft NE. of NE. corner of large house owned by J. H. Williams; 45 ft W. of center of rd.; in fence corner; in concrete post; standard tablet stamped "TT 13 TN 1933 811" 810.614 Reference mark; 70 ft NE. of tablet; 20 ft NE. of rd.; in root on SW. side of 36-in. red-oak tree; copper nail and washer 809.09 Hodgenville: in front of Larue County Courthouse: 1 ft E. of base of Lincoln's statue: in concrete sidewalk; standard tablet stamped "TT 21 TN 1933 730" (Tied by MGS, 1935) 729.959 Reference mark; 140 ft S. of tablet; on SW. side of square; in ME. corner of pavement; in front of Standard Oil Service Station (mark not described) 733.82 U. E., Hodgenville, 1.0 mi S. of, along U. S. Highway 31-E; 250 ft S. of two-story frame dwelling and opposite one-story frame dwelling; on NE. corner of E. headwall of concrete culvert; chiseled square 763.06 Hodgenville, 3.0 mi S. of, at main entrance to Lincoln's birthplace; 90.6 ft W. of hwy.; in concrete post; standard tablet stamped "TT 22 TN 1933 RESET 1958" 768.356 Reference mark; 60 ft S. of tablet; in root on NW. side of 24-in. elm tree; copper nail and

LINE 2.

By D. C. Antrobus, 1933; Book B 5084

washer

There are no permanent marks in this line on this quadrangle.

HODGENVILLE QUADRANGLE Book AV 52	125 KENTUCKY J. W. McLaughlin	37-085-42 4
	1948	7
	LINE 3.	Feet
By J. W. McLaughlin, 1948; Book AV 52		
"H 60 1935" (NGS)		463.126
Nelsonville; at public school grounds; in N. tablet stamped "TT 9 E 1930"	corner of concrete foundation of well; standard	472.719
Melsonville, 2.5 mi E. of, along graveled rd.; 75 ft E. of E. end of concrete bridge; 30 ft N. of center of rd.; in concrete post; standard tablet stamped "12 JWM 1948 506" (Reported destroyed, 1953)		
Reference mark: 75 ft W. of tablet: on NE. re	etaining wall of concrete bridge; chiseled square	508.39
	undation of; standard tablet stamped "TT 8 E 1930"	
		583.237
Reference mark; 130 ft S. of tablet; 15 ft W. of center of rd.; in root on E. side of 24-in. oak tree; copper nail and washer		
Nelsonville, 7.6 mi E. of, along dirt rd.; 2.0 mi SW. of Balltown; 65 ft NW. of junction of T-rd. NW. and U. S. Highway 31-E; 15 ft NE. of T-rd.; 2 ft SE. of fence corner; in concrete post; standard tablet stamped "13 JWM 1948 591"		591.081
Reference mark; 110 ft S. of tablet; 30 ft MV of concrete culvert; chiseled square	W. of center of U. S. Highway 31—E; on SW. headwall	585•53
	ighway 31—E; 100 ft N. of N. corner of house standing f hwy.; on NE. headwall of L—shaped concrete culvert;	582.07
Balltown; 21 ft E. of rd.; 18 ft S. to corner residence of J. W. Smith; in front yard; in "TT 7 E 1930 634"	r of log cafe building; 24 ft E. to W. corner of n concrete post; standard tablet stamped	633.762
	LINE 4.	
By J. E. McClane, 1950; Book AV 224		
"J 58 1935" (NGS)		783 .60 7
	section of T—rd. SW., opposite mail box of J. T. ce corner; in concrete post; standard tablet	931.922
Reference mark; 120 ft W. of tablet; at S. en ladies rest room; chiseled square	nd of Eat Shop; on SE. corner of walkway to	785.63
	of residence of Carter Underwood; 20 ft S., 30 fence corner; in concrete post; standard tablet	928•577

HODGENVILLE QUADRANGLE 125 KENTUCKY	37 - 085 -4 2
LINE 4 (Cont'd.)	5 Feet
Reference mark; 80 ft NE. of tablet; in root on S. side of 50—in. sugar tree; copper and washer	r nail 929.58
Ginseng, 0.3 mi NW. of post office; 15 ft E. and level with Y-rd. forks; 18 ft SW. of corner of barn; 14 ft N. of center of gateway to barn lot; 2 ft W. of wooden fence concrete post; standard tablet stamped "121 JEM 1950 544"	of SW. e; in 543.805
Reference mark; 140 ft SE. of tablet; in root on NE. side of twin trunk sycamore tre nail and washer	ee; copper 540.31
Ginseng, 1.5 mi NE. of, along creek bed and secondary rd.; 240 ft SE. of house of Wa 5 ft N., 45 ft W. of, and 2 ft higher than junction of rd. and private drive W.; i post; standard tablet stamped "122 JEM 1950 879"	alter Scaggs; in concrete 878.743
Reference mark; 75 ft ME. of tablet; in root on W. side of 30-in. elm tree; copper n washer	nail and 880.54
Attilla, 2.0 mi W. of; W. of T-rd. N.; 40 ft S. of center of rd. at Y-junction; 8 ft mail box; in concrete post; standard tablet stamped "123 JEM 1950 904"	t SW。 of 904.394
Reference mark; 70 ft NW. of tablet; in root on SE. side of 24—in. oak tree; copper washer	nail and 904.51
Attilla, O.l mi W. of grocery store of Charles Shaffner; at Y-rd. N.; 36 ft S., 8 ft l ft higher than center of grass triangle; 15 ft SE. of center of Highway 462; in post; standard tablet stamped "TT 51 AS 1950"	
/Jogs into Lefaman quadrangle/	
Raywick, 5.4 mi W. of, along State Highway 84, thence 0.8 mi S. along I—rd.; at right bend in rd. E.; at home of Mrs. Joseph La Rue; 5 ft S. and 12 ft W. and 1 ft lower extended intersection of rd.; 42 ft S. of center of rd. at drive; 40 ft W. of 42—i ash tree; 12 ft N. of telephone pole; 5 ft ENE. of vine covered fence; in concrete standard tablet stamped "TT 32 AS 1950 570"	r than in. twin
Reference mark; 63 ft E. of tablet; 15 ft S. of center of rd.; in W. base of 30-in. copper nail and washer	ash tree; 569.40
U. E., New Hope, 4.6 mi S. of; 12 ft E. and level with center of rd. at drain crossi schoolhouse; on SE. corner of rock culvert; chiseled square	ing; near 554.19
New Hope, 4.0 mi S. of along main rd. to State Highway 84; at second concrete bridge 57 ft NW. and 1 ft lower than junction of T-drive W.; 11 ft N. and 5 ft E. of cent concrete bridge; 5 ft NW. of center of rd.; in N. corner of railing of bridge; stamped "TT 31 AS 1950 561"	ter of
Reference mark; 590 ft S. of tablet; on M. end of W. headwall of concrete culvert; of square	
U. E., New Hope, 2.6 mi S. of; 13 ft E. and 1 ft lower than center of rd. at drain of on E. end of 30-in. culvert; chiseled square * New description- soad was been rebuilt S now 200ft, w of Lenter of new 5 S now used by farmed. to a 25 to g	625,82

HODGENVILLE QUADRANGLE	125 KENTUCKY	37 - 085-42 6	
LINE 4 (Cont'd.)		Feet	
New Hope, 2.0 mi S. of along main rd. to State Highway 84; at I—drive NE.; 40 ft S., 17 ft E. and 1 ft higher than center of rd.; 7 ft SE. of center of E. end of culvert; 4 ft SW. of SW. edge of gate; 2 ft W. of fence; in concrete post; standard tablet stamped "TT 30 AS 1950 682" (Reported destroyed, 1955)			
Reference mark; 275 ft SW. of tablet; or	n N. end of 24—in. concrete culvert; chiseled square	681 . 973	
U. E., New Hope, 0.8 mi S. of; 60 ft N. triangle; on S. end of 12-in. concrete	, 12 ft E. and 1 ft higher than center of traffic e culvert; chiseled square	579 .80	
"Q 60 1935" (NGS)		517.811	
New Hope, 1.1 mi N. of, along State High NE.; 21 ft SW. of 12—in. pear tree; 2 stamped "TT 29 AS 1950 528"	hway 52; 27 ft N., 19 ft W. and level with hwy. at Y-rd. ft E. of fence; in concrete post; standard tablet	528 .01 3	
Reference mark; 70 ft S. of tablet; on !	ME. corner of concrete headwall; chiseled square	528 .52	
New Hope, 2.9 mi N. of; 5 ft N., 36 ft N 6-in. cedar tree; 2 ft NE. of fencelin standard tablet stamped "TT 28 AS 1950	W. and 4 ft higher than junction of Y-rds.; 13 ft NE. of ne; 33 ft W. of center of main rd.; in concrete post; 0 667"	667.077	
U. E., New Hope, 3.7 mi N. of; 6 ft W. a bridge; on NE. corner of hand rail bas	and 1 ft higher than center of rd. at N. end of concrete se; chiseled square	521.91	
	Jogs into Lebanon quadrangle/		
"TT 7 E 1930 634" (Described in line 3)		633.762	
LINE 5.			
By J. E. McClane, 1950; Book AV 224			
"120 JEM 1950 929" (Described in line 4))	928.577	
2 ft higher than M. point of grass tra	Highway 84, thence S. 3.9 mi; 10 ft N., 18 ft W. and affic triangle at T⊸rd. N.; 40 ft NW. of 12—in. walnut ost; standard tablet stamped "127 JEM 1950 519"	518.812	
Reference mark; 90 ft NNE. of tablet; 6 chiseled square	ft E. of center of rd., on large boulder at drain;	514.10	
U. E., Howardstown, 2.2 mi SW. of; 60 fi field rd. SE.; on S. end of E. headwal	t S., 6 ft E. and 1 ft higher than center of rd. at 11 of small bridge; chiseled square	504.30	
Howardstown, 1.6 mi WSW. of; 20 ft S., 2 W.; in concrete post; standard tablet	22 ft W. and 1 ft higher than junction of abandoned rd. stamped "128 JEM 1950 515"	515.316	
Howardstown, 0.8 mi W. of along State Hi and 12 ft higher than hwy. at dirt I— standard tablet stamped "129 JEM 1950	ighway 84; 500 ft W. of steel bridge; 40 ft N., 28 ft E. rd. N.; 2 ft SW. of fence corner; in concrete post; 522"	522 .207	

.

,

HODGENVILLE QUADRANGLE	125 KENTUCKY	37 - 085-42		
LINE 6 (Cont'd.)		Feet		
U. E., Howardstown; 16 ft W. and level wi wooden bridge over stream; on W. end of chiseled square	ith center of State Highway 247; at W. end of small f N. rock wingwall; opposite large general store;	506.49		
"129 JEM 1950 522" (Described in line 5)		522.207		
LINE 7.				
By J. E. McClane, 1950; Book AV 224				
"K 60 1935" (NGS)		487.394		
U. E., Lyons, O.9 mi NW. of; 35 ft S., 33 at junction of State Highway 52 at Y-ro square	S ft E. and l ft lower than center of traffic triangle I. SW.; on S. end of concrete pipe culvert; chiseled	465.68		
Lyons, 1.0 mi NW. of, along State Highway 22 ft E. and 1 ft lower than center of 1.5 ft N. of hog wire fence, in concret "132 JEM 1950 463"	752, thence WNW. on gravel for 1.4 mi; 15 ft S., rd. at farm crossroads; 6 ft S. of large mail box, see post; standard tablet stamped	463.060		
Reference mark; 270 ft W. of tablet; on W	. end of S. headwall of culvert; chiseled square	465.15		
U. E., Lyons, 3.1 mi NW. of; 10 ft SW. an concrete bridge over stream; chiseled s	d 2 ft higher than center of rd.; at SE. end of quare	460.85		
than junction of I-rd. W., in concrete	nof L. L. Harned; 24 ft N., 20 ft W. and 8 ft higher post; standard tablet stamped "133 JEM 1950 496" Cerolal destroyed 1982 W. end of 24-in. concrete culvert; chiseled square	495 . 808		
Lyons, 5.8 mi NW. of; 66 ft S. and 4 ft higher than junction of Y-rd. forks; 38 ft N. and 8 ft E. of junction of private drive S.; at N. end of row of mail boxes; 1.5 ft W. of fenceline; in concrete post; standard tablet stamped "134 JEM 1950 838" Lyons, 8.6 mi W. of; 42 ft W., 18 ft S. and level with crossroads; 145 ft W. of small square log cabin; 28 ft NW. of intermittant stream; 7 ft NW. of mail box; in concrete post; standard tablet stamped "135 JEM 1950 893" Lyons, 8.6 mi W. of; 42 ft W., 18 ft S. and level with crossroads; 145 ft W. of small square log cabin; 28 ft NW. of intermittant stream; 7 ft NW. of mail box; in concrete post; standard tablet stamped "135 JEM 1950 893" Lyons, 8.6 mi W. of; 42 ft W., 18 ft S. and level with crossroads; 145 ft W. of small square log cabin; 28 ft NW. of intermittant stream; 7 ft NW. of mail box; in concrete post;		837.783		
		892.605		
	. end of concrete pipe culvert; chiseled square	891.95		
"TT 5 TN 1933 953" (Described in line 1)		952.469		
	LINE 8.			
By J. E. McClane, 1950; Book AV 224				
"135 JEM 1950 893" (Described in line 7)		892.605		

"TT 21 TN 1933 730" (Described in line 1)

Hodgenville; at N. edge of town; at bridge on State Highway 61 over Morth Fork Nolin River;

0.6 mi downstream from Douglas Creek; U.S.G.S. (Water Resources Branch) standard reference disk stamped "#2"

706.386

HODGENVILLE QUADRANGLE	125 KENTUCKY	37 - 085 -4 2
LINE 9 (Cont'd.)	•	10 <u>Feet</u>
"P 58 1935" (NGS)		716.498
	LINE 10.	
By J. E. McClane, 1950; Book AV 224		
"143 JEM 1950 779" (Described in line 9)		779.034
U. E., Hodgenville, 1.9 mi NE. of, thence 1.2 of rd. at private drive S.; on W. end of control of rd.	mi SE; 10 ft S., 6 ft W. and level with center crete pipe culvert; chiseled square	871.72
U. E., Leafdale, 1.5 mi W. of; 12 ft S. and 1 on E. end of concrete headwall; chiseled squ	ft higher than center of rd. at drain crossing; are	853.98
Leafdale; 170 ft SE. of crossroads at Kane's g Church; 37 ft SW. of center of rd. E., 6 ft l tablet stamped "146 JEM 1950 937 RESET 1952"	eneral store; 140 ft NW. of Oak Grove Methodist NW. of power pole, in concrete post; standard	936.024
Reference mark; 200 ft N. of tablet; on SE. enc chiseled square	d of comcrete porch at Kane's general store;	935•75
U. E., Leafdale, 1.5 mi SW. of; 15 ft S. and 1 over Creek; on S. corner of E. wingwall; chis	ft lower than center of rd. at E. end of bridge seled square	774.83
Hodgenville, 3.8 mi SE. of, along State Highway 14 ft S., 102 ft E. and 9 ft higher than crost tree; 1 ft N. of fenceline; in concrete post	y 210, thence 0.9 mi NE. along State Highway 470; ssroads; 90 ft WSW. of twin—trunked 10—in. oak ; standard tablet stamped "147 JEM 1950 839"	839.017
Reference mark; 147 ft WSW. of tablet; on W. er square	nd of 24—in. concrete pipe culvert; chiseled	830.80
U. E., Buffalo, 2.3 mi NE. of; 12 ft N., 30 ft 210 at crossroads; on E. end of 12-in. concre	E. and 1 ft lower than center of State Highway ete culvert; chiseled square	847.49
U. E., Buffalo, 1.7 mi NE. of; 6 ft S., 7 ft W. concrete bridge over stream; on S. headwall;	, and 1 ft higher than center of rd. at small chiseled square	784.30
"L 58 1935" (NGS)		758.483
LINE 11.		
By J. E. McClane, 1950; Book AV 224		
"146 JEM 1950 937 RESET 1952" (Described in lin	ne 10)	936.024
U. E., Leafdale, 2.4 mi E. of; 8 ft N., 20 ft 8 private drive N.; on top of large boulder pro	and level with center of secondary rd. at ojecting 6 in.; chiseled square	836.76
"128 JEM 1950 515" (Described in line 5)		515.316

HORIZONTAL CONTROL NORTH AMERICAN DATUM OF 1927

> UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

37-085-42 HODGENVILLE QUADRANGLE 125 KENTUCKY N3730-W8530/15 DIAGRAM NJ 16-9 WINCHESTER

Hardin, Larue, Marion, and Nelson Counties

Edition of 11/4/77

ELIZABETHTOWN


(126)

PR: CRY/rmm

Plane coordinates are based on Lambert projection, Kentucky, South Zone

Only the permanent marks are listed for control classified obsolete and are not shown on sketch

SHEPHERDSVILLE



(97)

DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered OBSOLETE and is included in this list for the purpose of identification only.

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.
IT 7 E 1930 634 II 8 E 1930 II 9 E 1930 II 4 IN 1933 469 II 5 IN 1933 953 II 6 IN 1933 869 II 13 IN 1933 811 II 21 IN 1933 730 II 22 IN 1933 RESET 1958 II 1 DWP 1948 KY II 28 DWP 1948 II 30 DWP 1948 II 31 DWP 1948 II 32 DWP 1948 II 32 DWP 1948 II 24 AS 1950 II 25 AS 1950 II 28 AS 1950 667 II 29 AS 1950 682 II 30 AS 1950 561 II 32 AS 1950 570 II 51 AS 1950	333363334444466455555
NGS	
M 58 1935 N 58 1935 Q 60 1935	5 6 5

STATION DESCRIPTION
PLANE COORDINATES, FEET

LATITUDE

LONGITUDE

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By J. R. Ellis, 1933; Book C9337

Balltown; 21 ft E. of centerline of rd.; 24 ft W. of W. corner of residence of J. W. Smith; in frontyard; 18 ft N. of log cafe building; in concrete post; standard tablet stamped "TT 7 E 1930 634"

X = 2,070,412

Y = 511,764

37 44 19.30

85 30 23.44

Icetown; in SE. corner of concrete foundation of schoolhouse; standard tablet stamped "IT 8 E 1930"

X = 2,051,658

Y = 509.013

37 43 52.51

85 34 16.98

Nelsonville; at public school grounds; in N. corner of concrete foundation of well; standard tablet stamped "TT 9 E 1930"

X = 2.031.938

Y = 508,401

37 43 46.76

85 38 22.46

By R. H. Lyddan, 1933; Book D842

Darlington School, 2.2 mi S. of; 10 ft N. of junction of Younger Creek to I-rd. S. to Ballinger School; 1 ft S. of fenceline; in concrete post; standard tablet stamped "TT 4 TN 1933 469"

PESTROYED

1953

X = 2.006.895

Y = 509.064

37 43 53.49

85 43 34.17

Middle Creek; 25 ft N. and 40 ft W. of crossroads; in SE. corner of pasture field of John Eulow; in concrete post; standard tablet stamped "TT 6 TN 1933 869"

X = 2.004.115

Y = 478,581

37 38 52.12

85 44 08.84

By R. H. Lyddan, 1933; Book D845

Hodgenville, 3.0 mi N. of; 45 ft W. of centerline of rd.; 75 ft NE. of NE. corner of large house owned by J. H. Williams; in fence corner; in concrete post; standard tablet stamped "TT 13 TN 1933 811"

X = 2.003.043

Y = 466,189

37 36 49,60

85 44 22-18

By R. H. Lyddan, 1933; Book D847

Hodgenville; in park opposite courthouse; 42 ft W. of centerline of Main Street; 1 ft E. of base of Lincoln Statue; in concrete sidewalk; standard tablet stamped "TT 21 TN 1933 730"

X = 2,002,758

Y = 451,606

37 34 25.41

85 44 25.74

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11 LONGITUDE 0 1 11

OBSOLETE MARKS (Cont'd.)

Hodgenville, 3.0 mi S. of; at main entrance to birthplace of Lincoln; 91 ft W. of centerline of hwy.; in concrete post; standard tablet stamped "TT 22 TN 1933 RESET 1958"

X = 2.004.864

Y = 436,364

37 31 54.71

85 43 59.62

By D. W. Pinkston, 1948; Book AH 84

Culvertown; in center of grassy triangle formed by junction of U. S. Highway 31E and State Highway 247; 88 ft S. of centerline of Highway 31E; 73 ft W. of SW. corner of residence; 3 ft S. of telephone pole; in concrete post; standard tablet stamped "TT 1 DWP 1948 KYM

X = 2.062.487

Y = 501.334

37 42 36.37

85 32 02.40

Boston, 5.2 mi SW. of, along U. S. Highway 62; 1.7 mi NE. of Chestnut Grove School; 200 ft SW. of white house; 27 ft NW. of centerline of Highway 62; 18 ft E. of barn; 14 ft E. of fence corner; 2 ft S. of garden fence: in concrete post; standard tablet stamped "TT 28 DWP 1948"

X = 2,001,155

Y = 514,289

37 44 45.16

85 44 45.62

Boston, 3.4 mi SW. of, along U. S. Highway 62, thence 1.3 mi SE. along State Highway 583, thence 1.1 mi SW., thence 1.4 mi S.; 100 ft N. of centerline of rd.; 2 ft N. and 2 ft E. of SW. leg of large steel cross-country powerline tower; in concrete post; standard tablet stamped "TT 30 DWP 1948"

X = 2.007.963

Y = 502.078

37 42 44.42

85 43 20.90

Middle Creek; 1.4 mi N. of; 32 ft E. of centerline of rd. at junction of T-rd. W.; 2 ft W. of fenceline; in concrete post; standard tablet stamped "TT 31 DWP 1948"

X = 2.002.761

Y = 485.119

37 39 56,76

85 44 25.66

Hodgenville, 5.0 mi S. of; 2.0 mi S. of entrance to Lincoln Memorial National Historic Park; 0.2 mi S. of bridge over South Fork Creek; 13 ft S. and 5 ft W. of SE. corner of South Fork Baptist Church; in concrete post: standard tablet stamped "TT 32 DWP 1948" (Not found, 1952)

X = 2,003,404

Y = 426.255

37 30 14.76

85 44 17.76

By A. Salloom, 1950; Book AH 194

New Hope, 2.9 mi N. of; 5 ft N. and 36 ft W. of 4 ft higher than junction of Y-rds.; 13 ft NE. of 6-in. cedar tree; 2 ft NE. of fenceline; 33 ft W. of center of main rd.; in concrete post; standard tablet stamped "TT 28 AS 1950 667"

X = 2.072.210 Y = 487.047

37 40 14.88

85 30 01.87

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11 LONGITUDE

OBSOLETE MARKS (Cont'd.)

New Hope, 1.1 mi N. of, along State Highway 52; 27 ft N. and 19 ft W. of centerline of hwy. at junction of Y-rd. NE.: 21 ft SE. of 12-in. pear tree; 2 ft E. of fenceline; in concrete post; standard tablet stamped "TT 29 AS 1950 528"

X = 2.069.844 Y = 478.689

37 38 52.30

85 30 31.63

New Hope; 105 ft SE. of station, along L. & N. RR.; 3 rails W. of post office; 36 ft W. of stone steps of brick house on hill; 5 ft N. of fenceline; in rock outcrop; NGS standard disk stamped "Q 60 1935"

X = 2.069.913 Y = 473.467

37 38 00-67

85 30 30.87

New Hope, 2.0 mi S. of, along main rd. to State Highway 84; at I-drive NE.; 40 ft S. and 17 ft E. of and 1 ft higher than centerline of rd. at junction of drive NE.; 7 ft SE. of E. end of culvert; 4 ft SW. of SW. edge of gate; 2 ft W. of fenceline; in concrete post; standard tablet stamped "IT 30 AS 1950 682" (Reported destroyed, 1955)

X = 2.071.311

Y = 464.054

37 36 27,57

85 30 13.81

New Hope, 4.0 mi S. of; at second concrete bridge over creek; 57 ft NW. of junction of drive W.; 5 ft NW. of center-) line of rd.; 11 ft N. and 5 ft E. of center of concrete bridge; in N. corner of concrete bridge railing; standard tablet stamped "TT 31 AS 1950 561" 300 ft. w. of center of concrete bridge.

X = 2.069.708 Y = 455.239

37 35 00.46

85 30 34.00

Raywick. 5.4 mi W. of, along State Highway 84, thence 0.8 mi S. along T-rd.; at right-angle turn in rd. E.; at residence of Mrs. Joe La Rue; 42 ft S. of centerline of rd. at junction of driveway; 5 ft S. and 12 ft W. of extended centerline of rd.; 40 ft W. of 42-in. twin ash tree; 12 ft N. of telephone pole; 5 ft ENE. of vine-covered fence; in concrete post; standard tablet stamped "TT 32 AS 1950 570"

X = 2,069,890 Y = 446.121

37 33 30.30

85 30 32,03

Attilla, O.l mi W. of grocery store of Charles Shaffner; 36 ft S. and 8 ft E. of center of grassy triangle formed by junction of Y-rd. N.; 15 ft SE. of centerline of State Highway 462; in NW. corner of tobacco patch; in concrete post; standard tablet stamped "TT 51 AS 1950"

X = 2.070.122 Y = 426.245

37 30 13.78

85 30 29.78

Hodgenville, 0.7 mi S. of post office, along State Highway 61; 0.9 mi S. of Masonic Temple Building; 120 ft M. and 24 ft E. of centerline of hwy. at junction of drive to residence of C. Cooksey: 288 ft SE. of SE. corner of green-roofed house; 11 ft SW. of SW. corner of old one-story house of D. Welther; in concrete post; NGS standard disk stamped MM 58 1935 (Reported disturbed, 1950)

X = 2.003.917

Y = 447.275

37 33 42.59

85 44 11.36

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 9 17

LONGITUDE 0 1 11

OBSOLETE MARKS (Cont'd.)

Hodgenville; at NW. corner of two-story brick Masonic Temple Building; in N. end of wall between W. side of building and E. side of door of cleaning establishment; NGS standard disk stamped "N 58 1935"

X = 2.002.833 Y = 451.446

37 34 23.83

85 44 24.81

Hodgenville, 0.7 mi N. of, along State Highway 61, thence 0.5 mi N. along graveled rd.; 18 ft N. and 20 ft W. of centerline of rd. at junction of driveway to residence of W. Cubbings; 5 ft E. of fenceline; 4 ft NE. of NE. corner of white concrete block driveway pillar; 2 ft NE. of telephone pole; in concrete post; standard tablet stamped "TT 24 AS 1950"

X = 2.003.682

Y = 457.713

37 35 25.79

85 44 14.26

Middle Creek, 1.0 mi S. of, along graveled rd.; at NW. corner of land of G. W. Corum; 8 ft S. and 19 ft W. of centerline of rd. at junction of drive W.; 8 ft W. of mailbox; in concrete post; standard tablet stamped "TT 25 AS 1950"

X = 2.003.262

Y = 473.549

37 38 02.37

85 44 19.45

MARK TIED BY NGS

By R. H. Lyddan, 1933; Book D842

Ballinger School; 140 ft NW. of; 8.0 mi E. of Elizabethtown; 80 ft S. and 140 ft E. of centerline of rd. at junction of rd. S. to Middle Creek; 140 ft NW. of schoolhouse; in frontyard; in concrete post; standard tablet stamped "11 5 IN 1933 953" TED OTTED 1982

X = 2,004,813.33 Y = 492,613.14

37 41 10.849

85 44 00.121